

Cabinet Construction

1. Full overlay door panel, 3/4" thick door panel
2. 4 to 6-way adjustable European hidden metal hinges (soft-close hinges available)
3. Adjustable, 3/4 shelf, 5/8" thick cabinet-grade plywood, metal shelf rests
4. Dovetail drawer, 1/2" thick solid wood sides
5. Full extension, under-mounted, soft-close, steel concealed drawer glides
6. 1/2" thick cabinet grade plywood box
7. Metal bracket reinforcements for base cabinets



Fine Cabinet Finishes

1. The finest maple wood is sanded until smooth and vacuumed.
2. An equalizer stain is applied to balance the base color of the wood.
3. A toner is then applied to establish color uniformity.
4. A deep penetrating stain is then applied to reveal the hidden beauty of the natural grain.
5. All stained surfaces are then hand-rubbed and wiped of excess stain, and then slowly air-dried.
6. A wood sealer is then applied, penetrating all exposed wood surfaces for uniform protection.
7. All surfaces are hand-sanded, providing a smooth, consistent surface.
8. A glaze is applied by hand (if applicable).
9. A color consistency examination is performed with additional touch-up if needed.
10. A final protective top coat is applied, maximizing resistance to scuffing, moisture, fading and most household chemicals.

